

**F**

Model		F-500	F-800	F-1000	F-1300	F-1600 /F-1600HL	F-2200
Specifications							
Max. input horsepower.	HP (kw)	500 373	800(597)	1000(746)	1300(969)	2200 1640	1600(1176)
Rated pump speed.	spm	165	150	140	120	105	120
Max. fluid cylinder liner bore.	in. (mm)	6 3/4"(171)	6 3/4"(171)	6 3/4"(171)	7"(177.8)	9"(230)	7"(177.8)
Stroke	in. (mm)	7.5" (191)	9" (229)	10" (254)	12" (304.8)	14" (356)	12" (304.8)
Ratio of gears		4.288:1	4.185:1	4.207:1	4.206:1	3.512:1	4.206:1
Valve pot, API number		API 5	API 6	API 6	API 7	API 8	API 7
Overall dimension(l*w*h) X X	in. (mm)	144×63.5×62 (3658×1613×1573)	156×69.5×66.7 (3963×1765.4×1694)	168×69.5×71.7 (4269×2057.4×1822)	174×69.5×79 (4426×2057.4×2008)	226×119×124 5740×3021×3161	192×129×82 (4875×3265×2080)/204×129×82 (5175×3265×2080)
Weight-complete, less sheave.	lbs. (kg)	21540 9770	26603 (12067)	33770 (15318)	45650 (20707)	94972 43080	46820/55380 0 (27500/25500)

**F**

		<b>F-500</b>	<b>F-800</b>	<b>F-1000</b>	<b>F-1300</b>	<b>F-1600 /F-1600HL</b>	<b>F-2200</b>
"	HP (kw)	500 373	800(597)	1000(746)	1300(969)	1600(1176)	1600(1176)
.	spm	165	150	140	120	120	120
"	in. (mm)	6 3/4"(171)	6 3/4"(171)	6 3/4"(171)	7"(177.8)	7"(177.8)	7"(177.8)
	in. (mm)	7.5" (191)	9" (229)	10" (254)	12" (304.8)	12" (304.8)	12" (304.8)
		4.288:1	4.185:1	4. 207:1	4.206:1	4.206:1	4.206:1
		API 5	API 6	API 6	API 7	API 7	API 7

**P-2200**

model

**P-2200**

	<b>P-2200</b>
	164      220    " "
	105    /
	355.6mm   14"
	3.969
	417    /
	51.7MPa    (527.3kg.f/cm <sup>2</sup> )
	77.55MPa    (791kg.f/cm <sup>2</sup> )
	API 8#
	<div style="display: flex; justify-content: space-between; align-items: center;"> <span>"</span> <span>"</span> </div> <div style="display: flex; justify-content: space-between; align-items: center;"> <span>230mm</span> <span>228.6mm(9")</span> </div>

## ZMF-2200

泵型号 model	<b>ZMF-2200</b>
额定输入功率 Rated input power	1642 千瓦 ( 2200 马力 ) 1642 kW (2200HP)
额定冲次 Rated stroke	117 冲/分 stroke/min 1642 kW (2200HP)